

WAM Series

WAM1202



12" Panel Mount Touch Panel PC (Android)



IP65



Fanless



TFT LCD





PCAP



Panel Mount



- 4:3 Ratio with 12" True-Flat PCAP touch
- Cortex-A55 Quad Core Processor
- Aluminum Alloy Housing
- Fanless & Front Panel IP65
- Support Phoenix type connector for DC power input
- Supports panel mount, wall mount, VESA, and desktop stand



Production Line / HMI Controller / Machine Vision / IIoT Gateway / Building Automation

Specification

WAM1202

Display

Display Type	12" TFT LCD
Resolution	1024 x 768
Brightness	300 nits (Optional to 1000 nits)
Touch Panel	10 Points Multiple PCAP touch
Aspect Ratio	4:3

Main System

CPU	Quad-core Cortex-A55 RK3568 Processor
	Quad-core Cortex-A55 Quad-Core +
	Quad-core Cortex-A76 RK3588 Processor (Optional)
GPU	Mali-G52 for RK3568
	Mali-G610 for RK3588
Memory	2GB (Max.4GB)
Storage	16GB (Max.32GB)
OS Support	Android 12
Function Support	WiFi 802.11 a/b/g/n/ac 2.4G (External Antenna)
	Bluetooth 4.2
	RTC
	UBOOT
IO Ports	1 x Phoenix type connector (2-pin)
	1 x DC-in
	2 x USB3.0
	1 x RJ-45
	1 x HDMI
	1 x SIM card slot
	1 x TF card slot
	1 x Audio (Mic-in & Line-out)
	2 x DB9 (RS232)
	1 x Power Button

Physical

Internal Speaker	2x 2W
Power Adapter	DC 24V/2.5A
Mounting	Panel Mount, VESA 75 x 75 mm & 100 x 100 mm,
	Wall mount, Desktop stand
Housing	Aluminum Alloy Housing
Standard Accessory	Power Adapter
	Clamp Mount Kit
Product Dimension	312.3 x 250.8 x 62 mm
Product Weight	3 kg

Environment

Rugged Feature	Front IP65
Certification	CE, FCC Class B
Operating Temperature	-10°C ~ 60°C
Storage Temperature	-20°C ~ 70°C
Relative humidity	95% RH non-condensing

Overview

Unit : mm

