

WCS Series

WCS3200



32" Commercial Entry Windows Touch Panel PC



- 32" Windows System
- Intel® Pentium N4200 Processor
- Professional Metal Housing
- Passive Cooling Fanless Design
- True Flat With 10 Points PCAP Touch
- Rich I/O Ports Provide Excellent Peripheral Connectivity



Amusement and Entertainment Device



KIOSK



Self-service Terminal



Interactive Digital Signage



Gambling Machine

Specification

WCS3200

Display

| | |
|----------------|--|
| Display Type | 32" TFT LCD |
| Resolution | 1920 x 1080 |
| Brightness | 400 nits |
| Touch Panel | 10 Points Projected Capacitive Touch Panel |
| Viewing Angle | Horizontal 178° / Vertical 178° |
| Contrast Ratio | 1200:1 |

Main System

| | |
|----------------|--|
| CPU | Intel® Pentium N4200 Processor |
| GPU | Intel UHD Graphics |
| Memory | 4GB DDR3 |
| Storage | 64GB SSD |
| OS Support | Windows 8, Windows 10, Linux |
| LAN Controller | WLAN: 802.11 b/g/n SiP Wireless Module |
| Communication | Bluetooth 4.0 |
| IO Ports | 2 x USB3.0 6 x USB2.0 1 x Micro USB2.0 1 x LAN 1 x Combo JACK 1 x SPDIF 1 x SD Card Slot 2 x Pogo Pin (Right, Bottom) |

Physical

| | |
|--------------------|----------------------------|
| Audio | 2 x 5W Speaker |
| Ventilation | Fanless |
| Color | Black |
| Mounting | VESA Mount 100 x 100 |
| Housing | Metal |
| Power Adapter | DC 12V/5A, 60W |
| Standard Accessory | 1 x Power Adapter (12V/5A) |
| Product Dimension | 769 x 470.5 x 45.6 mm |
| Product Weight | 10.54kg |

Environment

| | |
|-----------------------|----------------------------|
| Certification | CE, FCC |
| Operating Temperature | 0°C ~ 40°C |
| Storage Temperature | -20°C ~ 60°C |
| Relative Humidity | 10% ~ 90% (Non-Condensing) |

Dimensions & Drawing

Unit : mm

